







Exclusive Display Center:

Noorjahan Tower, (1st Floor) 2 No. Link Road, Bangla Motor, Dhaka-1000

Corporate Headquarters:

MF Tower: Plot- GA-95/C, Pragati Sarani Gulshan 1 Link Road, Dhaka-1212 Tel: +88-02-9847141, +88-02-9846442, +88-02-58817175 Fax: +88-02-9856110, Email: info@xceramics.com

⊕ xceramics.com
☐ monalisatilesbd

(+8801844004046, 48 & 60









A VENTURE INCEPTED BY **ITALIANS**

Italian fashion is not just restricted to clothing and X Monalisa is a testament to its versatility. X Monalisa designs ooze scintillating glamour inspired by Italian fashion.

www.xceramics.com



X Monalisa is Bangladesh's leading ceramic tiles brand, which was established in the year 2013 under the umbrella of X Ceramics Group. X Monalisa has a constant focus on design, research and technological advancement to accomplish excellence in product. This consistent endeavor to innovate better has helped X Monalisa to offer a comprehensive portfolio of porcelain tiles for residential and commercial spaces.

X Monalisa has created a foundation of success based on its caliber of understanding the needs of our customers and delivering high quality designs that are fashionable, safe and long-lasting.

X Monalisa's core values of quality, innovation and respect are reflected by:

- Its desire to make new headways in the technological front.
- Endeavor to introduce Italian designs and culture in Bangladesh through the creativity of the products.
- Responsible actions to protect the environment with safe and smart processes to ensure future generations can experience the gift of nature.

The capabilities of X Monalisa are extensive, which focus on research and innovation in the ceramic industry, but also push the mantle of inspiring new trends and creating scintillating home & office décors. Monalisa aspires to be a pioneer of marvelous creations which is taking the brand high above its peers to leave behind an unforgettable legacy of artistry.



CONTENTS

Page (04 - 09)

30X60 cm (Wall)

Royal Series | Super Glossy

Page (10 - 13)

30X60 cm (Wall) 30X30 cm (Floor) Rock-X Series | Matt

Page (14 - 17)

30X60 cm (Wall) Sugar Rustic Series | Matt

Page (18 - 25)

30X60 cm (Wall) HD Wall Tiles | Glossy

Page (26 - 41)

30 x 45 cm (Wall) HD Wall Tiles | Glossy, Matt

Page (42 - 43)

30 x 45 cm (Wall) Sugar Rustic Series | Matt

Page (44 - 45)

25 X 40 cm (Wall) Wall Tiles | Glossy Page (46 - 61)

20 X 30 cm (Wall) Wall Tiles, 3D Wall, Royal Series | Glossy

Page (62 - 68)

80 x 80 cm (Floor) PGVT Series | Glossy

Page (69 - 77)

60 x 60 cm (Floor)
PGVT Series, MHGT Series, MGVT Javnamaz | Glossy

Page (78 - 79)

60 x 60 cm (Floor)

Page (80 - 83)

60 x 60 cm (Floor) Germi Proof Solido | Glossy

Page (84 -89)

40 x 40 cm (Floor) Transparent Glaze Series | Glossy

Page (90 - 91)

30 x 30 cm (Floor) Anti Slip | Matt Page (92 - 97)

 60×60 cm (Floor) | 40×40 cm (Floor) 30×30 cm (Floor) Stone Shield Series | Matt

Page (98 - 99)

30 x 60 cm (Stair) Stone Shield Stair Series | Matt

Page (100 - 101)

60 x 60 cm | 40 x 40 cm 30x30 cm | 30x60 cm Homogeneous Series Stair & Floor Tiles | Semi-Glossy

Page (102 - 107)

60 x 60 cm | 30 x 60 cm 15 x 60 cm (Floor)

Royal Plank Series | Matt

Page (108 - 111)

30 X 30 cm (Floor)

Outdoor Series | Matt

Page (112 - 113)

30 X 30 cm (Floor)

Parking Series | Matt



FASCINATING & MESMERISING DESIGNS

ROYAL TILESSIZE REDEFINED, LUXURY REDESIGNED

X Monalisa Italian fashion tiles present a world of inventive designs to allure you and turn your spaces into a liveliness of splendor.

Size: 30X60 cm

Never paint dreams on nightmares Should paint your own reality

With a niche selection of 13 designs, this series is an amalgamation of elegance, glamour, luxury and sensuality, capturing different temperaments that are truly reflective of your unique style.



ROYAL SERIES

Wall Tiles | Super Glossy 30 x 60 cm



MWRS 630001



MWRS 630002



ROYAL SERIES

Wall Tiles | Super Glossy 30 x 60 cm



MWRS 630006



MWRS 630035









ROYAL SERIES

Wall Tiles | Super Glossy 30 x 60 cm




MWRS 630003



MWRS 630004



MWRS 630005




MWRS 630030

MWRS 630031





MWRS 630036



MWRS 630032



ROYAL SERIES

Wall Tiles | Super Glossy 30 x 60 cm



MWRS 630033









FASCINATING & MESMERISING DESIGNS

WALL & MATCHING FLOOR

X Monalisa Italian fashion tiles present a world of inventive designs to allure you and turn your spaces into a liveliness of splendor.

ROCK-X SERIES

Size: 30X60 cm, 30x30 cm (Floor)

Touch and feel of these tiles are like real stones with guaranteed colorfastness.







MRS 60301 L



MRS 60301 HL



MST 30301





Series | Matt 30 x 60 cm (Wall) 30 x 30 cm (Floor)



MRS 60305 L



MRS 60305 HL



MRS 60305 D





CREATE YOUR MODERN DREAM

Tent for sugar rustic series.





Sugar Rustic Series Wall Tiles | Matt 30 x 60 cm



MRTW 631 W





MRTW 635 BRW



MRTW 639 W





MRTW 641 W















FASCINATING & MESMERISING DESIGNS

WALL & MATCHING FLOOR

X Monalisa Italian fashion tiles present a world of inventive design to allure you and turn your spaces into a liveliness of splendor.

Size: 30x60 cm, 30x45 cm, 25x40 cm, 20x30 cm (Wall) & 30x30 cm (Floor)

An infusion of art, experience and innovation in a size of 20x30 cm, 25x40 cm, 30x45 cm & 30x60 cm



MHDW 3622 GY



MHDW 3616



MHDW 3609



MHDW 3608










MHDW 3628 L



MHDW 3628 HL



HD Wall Tiles | Glossy 30 x 60 cm



MHDW 3630 L



MHDW 3630 HL



MHDW 3630 D







MHDW 3632 D



MHDW 3632 HL



HD Wall Tiles | Glossy 30 x 60 cm



MHDW 3633









Glaze and Shade is sure to make your **WALL** look great.



HD Wall Tiles | Matt 30 x 45 cm

2,842	
	SEA .
B 200 S	

MHDW 3003 DL



HD Wall Tiles | Matt 30 x 45 cm



MHDW 3007 L



MHDW 3007 HL



MHDW 3007 D





MHDW 3076 GY



MHDW 3076 BR






MHDW 3081 L



MHDW 3081 HL



MHDW 3081 D





MHDW 3082 L



MHDW 3082 HL



MHDW 3082 D



HD Wall Tiles | Glossy 30 x 45 cm



MHDW 3084 L



MHDW 3084 HL



MHDW 3084 D



MHDF 3084 (AS)









MHDW 3090 L



MHDW 3090 HL



MHDW 3090 D



HD Wall Tiles | Glossy 30 x 45 cm



MHDW 3091 L



MHDW 3091 HL



MHDW 3091 D





MHDW 3092 L




MHDW 3092 HL



MHDW 3092 D





MHDW 3094 L



MHDW 3004 HI



MHDW 3094 D





MHDW 3058 HL



MHDW 3059 L



MHDW 3063 L



MHDW 3085 GY



MHDW 3085 YL



MHDW 3086



MHDW 3066 BG



MHDW 3066 BR





MHDW 3095 L



MHDW 3005 HI



MHDW 3095 D



HD Wall Tiles | Glossy 30 x 45 cm



MHDW 3096 L



MITDW/ 2004 III



MHDW 3096 D



Sugar Rustic Series Wall Tiles | Matt 30 x 45 cm



MRTW 348



MRTW 349



Sugar Rustic Series Wall Tiles | Matt 30 x 45 cm



MRTW 354



MRTW 355











MHDW 2501 L



MHDW 2501 D



MHDW 2502 L




MHDW 2502 D



MHDW 2530 (White)



MHDW 2566 L



HD Wall Tiles | Glossy 25 x 40 cm



MHDW 2570 L



MHDW 2570 HL



MHDW 2570 D









Super Digital Series Wall Tiles | Glossy 20 x 30 cm



MWD 262 L



MWD 262 HL 2



MWD 262 D



Super Digital Series Wall Tiles | Glossy 20 x 30 cm



MHDW 272 L



MHDW 272 HL



MHDW 272 D







Super Digital Series Wall Tiles | Glossy 20 x 30 cm



MHDW 275 L



MHDW 275 HL



Super Digital Series Wall Tiles | Glossy 20 x 30 cm



MHDW 276 L



MHDW 276 HL



MHDW 276 D









Super Digital Series Wall Tiles | Glossy 20 x 30 cm



MWD 277 L



MWD 277 HL




MWD 277 D



MWD 232 L



MWD 232 D



MWD 252 BL

MWD 249



MWD 247



MWD 254 PK



MWD 263



MWD 266



Analog Digital Series Wall Tiles | Glossy 20 x 30 cm



MW 2052







Analog Digital Series Wall Tiles | Glossy 20 x 30 cm



MW 2076 BL



Analog Digital Series Wall Tiles | Glossy 20 x 30 cm



MW 2030 (White)



MW 2029 (Black)



MW 2032 BK



MW 2034 GY



MW 2035



MW 2035 BR



MW 2035 BL



MW 2038 BK



MW 2063

MW 2067





MW 2069



MW 2074 L



MW 2074 HL



MW 2068





MWD 201 L



MWD 201 HL



MWD 201 D



MWD 211



MWD 212



MWD 214



MWD 216 L



MWD 216 HL











MWD 217 L





MWD 219 L



MWD 220 L



MWD 217 HL

MWD 217 D



MWD 218 HL



MWD 219 HL



MWD 220 HL



MWD 219 D



MWD 220 D



3D Wall | Glossy 20 x 30 cm



MWD 215 L



MWD 215 HL















MWD 221 L



MWD 221 HL



MWD 221 D



3D Wall | Glossy 20 x 30 cm



MWD 222 L



MWD 222 HL









MWD 223 L



MWD 223 HL



MWD 223 D



Royal Series Wall Tiles | Glossy 20 x 30 cm



MRSW 23000



MRSW 23001



MRSW 23002



MRSW 23003







Let The Space Inspire

Ultra glossy polished glazed vitrified tiles

Size: 80X80 cm, 60X60 cm

Unmatched luxury.....

Beauty is as big as your visions **EXPANSIVE & ELEGANT**Size: 80x80 cm & 60x60 cm





MGVT Series Floor Tiles | Glossy 80 x 80 cm



MGVT 8001



MGVT 8002

Giossy Percelain



MGVT Series Floor Tiles | Glossy 80 x 80 cm



MGVT 8006



MGVT Series Floor Tiles | Glossy 80 x 80 cm



MGVT 8007



MGVT Series Floor Tiles | Glossy 80 x 80 cm



MGVT 8008



MGVT Series Floor Tiles | Glossy 80 x 80 cm



MGVT 8010




MGVT 8009

Glossy Porcelain



MGVT Series Floor Tiles | Glossy 60 x 60 cm



MGVT 6014



MGVT 6048 (White)





MGVT Series Floor Tiles | Glossy 60 x 60 cm



MGVT 6020



MGVT 6012

70 Dept. Cleasy Perculain (Floor) Strength



MGVT Series Floor Tiles | Glossy 60 x 60 cm



MGVT 6047



MGVT 6013





MGVT Series Floor Tiles | Glossy 60 x 60 cm



MGVT 6074



MGVT 6080





MGVT Series Floor Tiles | Glossy 60 x 60 cm



MGVT 6091



MGVT 6081





MGVT Series Floor Tiles | Glossy 60 x 60 cm



MGVT 6094



MGVT 6082





MGVT Series Floor Tiles | Glossy 60 x 60 cm



MGVT 6099



MGVT 6084



MHGVT Series Floor Tiles | High Glossy 60 x 60 cm




MHGVT 6200

'Strength of Porcelain and the Finish of Mirror'



MGVT Jaynamaz Floor Tiles | Glossy 60 x 60 cm



MGVT 6010










6 LAYER GERMI PROOF TILES ANTIMICROBIAL TECHNOLOGY



Necessity is the mother of invention. As the world continues to face a prolonged massive health crisis during this global pandemic, surface and solution expert Xceramics Group respond faster to the situation and invented the most advanced innovative surface in the history of ceramic industry in the form of Jaynamaz motif tiles suitable for mosque. Keeping in mind the beautiful Islamic architecture, mass gathering of people inside mosque and health safety issues, our Jaynamaz tiles are coated with Germi Proof layer, a special antiviral & antibacterial technology that prevents us from virus and bacteria. Patented Stone Shield layer makes the tile 10 times more durable and anti-slip. This tile has been tested in independent labs across the world including Bangladesh Council of Scientific & Industrial Research.

GERMI PROOF TILES CHARACTERISTICS

ANTIMICROBIAL TECHNOLOGY



Bacteria and Virus have a short life on Germi proof tile surface. The Germi proof layer is burned firmly into the tile glaze and that's why the antimicrobial effect does not diminish but is rather retained over the entire service life of the tile. This innovative technology therefore sets entirely new standard inside mosque where particular cleanliness and hygiene is a major concern.

10X DURABLE



The unique Stone Shield glaze composition applied on the surface of a vitrified tile body ensures resistance to day to day scratches and wear & tear when applied in any high traffic area. This enables the tile to retain the original design printed on the surface and maintain the aesthetics. Abrasion test result shows that this tough patented surface remained unscratched and shinned up to 54000 revolutions which is 10 times more durable than any other tiles in the market.

ANTISLIP



Chances of a mishap to your loved ones are greatly increased on the slippery floors in a mosque due to water from ablution. The anti-slip properties of Jaynamaz tiles reduces the chances of accident which may happen due to a sudden fall.

STAIN RESISTANT



At tile is affected to staining because of micro pore holes on top of the surface. In our Jaynamaz tiles, Stone Shield layer completely fills all the micro pore holes. As a result, the tile becomes highly abrasion & stain resistant for longer duration and 100% hydiene.

T


STONE STRENGTH

The breaking test shows the tile remain intact at 3100N+ force making it harder than natural stone.



ANTI-ODOUR

In our Jaynamaz tiles, there is no room for bad smells. The unique property of the tile eliminates the molecules that causes unpleasant smells.



Jaynamaz Germi Proof Floor Tiles | Matt 60 x 60 cm





MGPJ 6110











USP of Solido Germi Proof Nano Mirror Polished

- The most advanced innovative surface,
- Protect from harmful germs,
- Unique solid Colors
- Nano Mirror Polished
- Easy to maintain & clean,
- Safe for kids,
- Sizes available: 60x60cm

Features and Applications of Germi Proof Tiles:

Hygienic, anti bacterial and microbes resistant, anti-infective, deodorant, easy maintenance and cleanable.

GERMI PROOF TILES

ANTI MICROBIAL TECHNOLOGY

GERMI PROOF LAYER



THE MOST ADVANCED INNOVATIVE SURFACE



Germi Proof Solido

Floor Tiles | Glossy 60 x 60 cm











Transparent Glaze Series Floor Tiles | Glossy 40 x 40 cm



MTG 4050



MTG 4051



Transparent Glaze Series Floor Tiles | Glossy $40 \times 40 \text{ cm}$



MTG 4052



MTG 4055



Transparent Glaze Series Floor Tiles | Glossy 40 x 40 cm



MTG 4054



MTG 4053



Transparent Glaze Series Floor Tiles | Glossy 40 x 40 cm



MTG 4057



MTG 4059



Transparent Glaze Series Floor Tiles | Glossy 40 x 40 cm



MTG 4067



MTG 4068



Transparent Glaze Series Floor Tiles | Glossy 40 x 40 cm



MTG 4069



MTG 4070







X Ceramics a pioneer in Bangladesh's tiling industry, which has been proven time and again by its passion for ceramics. Through the high prowess and experties of its in-house research & development department and international collaboration, X Ceramics has become a surface and solution guru.

With a thought of care and protection for the young buds and seniors of our families, we specially developed an innovative and feature-rich range of Anti-Slip Tiles. Crafted for the various slippery areas in homes, this Anti-Slip range is a welcome addition into our portfolio of products that touch lives. Along with high durability and resistance to abrasions, the co-efficient of friction doesn't diminish on our Anti-Slip Tiles as it does on general floors. These exceptional features make these tiles ideal for application in kitchens and bathrooms.

All the matching floors of our kitchen and bathrooms wall tiles have Anti-Slip properties.









MHDF (AS) 3081









MHDF (AS) 3069









MHDF (AS) 3084










The unique STONE SHIELD glaze composition applied on the surface of a vitrified tile body ensures resistance day to day scratches and wear & tear when applied in any high traffic area. this enables the tile to retain the original design printed on the surface and maintain the aesthetics.



STRENGTH TEST:

STONE SHIELD technology tiles are not only resistant to abrasion and stain, it is also harder than natural stone or any other tiles. The strength test shows the breaking comparison of Homogeneous tiles & Stone Shield tiles when constant force is applied to tile body.



**Ceramics | www.thestoneshield.com | www.xceramics.com

ABRASION RESISTANT:

The abrasion comparison test was done to observe the performance of STONE SHIELD with other widely used tiles such as Marble, Homogeneous, Double Charge, Gres Porcelain. While other tiles got noticeable amount of scratches at only 5000/10000 revolutions and failed to pass the test. STONE SHIELD tiles remain unscratch and shine up to 54000 revolutions. This is far beyond any other available tiles in the market. This tough surface gives longer life to the tiles in terms of abrasion resistance and well suited for any kind of traffic.











₩10,000 掛54,000+ rev.

STONE SHIELD Tiles 54,000+ Revolutions Passed

₩10,000

Abration resistant of a tile is measured (ISO 10545) as per the methods adopted by PEI Inc. (Porcelain Enamel Institute), USA.







Stone Shield Series Floor Tiles | Matt 60 x 60 cm



MST 6103



MST 6108



Stone Shield Series Floor Tiles | Matt 60 x 60 cm



MST 6106



MST 6110





Stone Shield Series Floor Tiles | Matt 40 x 40 cm



MST 4014



MST 4010



Stone Shield Series Floor Tiles | Matt 40 x 40 cm



MST 4013





















MSTP 632

MSTP 634











Homogeneous Series Stair & Floor Tiles | Semi-Glossy 30 x 30 cm & 26 x 30 cm

Size: 30 x 30 cm

Size: 26 x 30 cm

MH STP 362 (Pink)

MH STP 363 (Green)



MH STP 360 (Off White)



MH 302 (Pink)

MH 300 (Off White)



MH 303 (Green)



Homogeneous Series Stair & Floor Tiles | Semi-Glossy 60 x 60 cm, 40 x 40 cm & 30 x 60 cm

Size: 60 x 60 cm



MH 600 (Off White)



MH 4002 (Green)



MH 4000 (Off White)

Size: 40 x 40 cm



MH 4001 (Pink)







S E R I E S

From times gone by people used to depend on wood in making shelter-it is an age old relationship between human being and tree History dates back to 1625, French parquetry, and marquetry patterns began to appear These are the floors made from pieces of wood out by hand and fitted together in contrasting three dimensional decigns.

In modern time X Ceramics group came up wit vitrified floor tile which resembles natural wood With wooden plank's textures we brough nature, houses, and human beings together in higher unity. Different pieces of wood represer moods with their rare textures. Choosing texture will represent your persona. A hous adorned with wood takes its dwellers to the nature. These wooden planks will shape your present with the blend of past for your forthcoming future with their deep rooted life





Royal Wood Series Floor Tiles | Matt 60 x 60 cm



MRS 66623







Royal Wood Series Floor Tiles | Matt 60 x 60 cm



MRS 66625



MRS 66626







Royal Plank Series Floor Tiles | Matt 15 x 60 cm



MRS 15623







Royal Plank Series Floor Tiles | Matt 15 x 60 cm



MRS 15628











Transform any external space with our outdoor tile series. Bring your outdoor space to life with these tiles. Suitable for patios, balconies and decking, with a range of high-quality durable tiles. Styles, textures and colors to suit any requirement.

SIZE: 30X30 CM



Outdoor Series Floor Tiles | Matt 30 x 30 cm



MOD 358



MOD 353



MOD 355



Outdoor Series Floor Tiles | Matt 30 x 30 cm



MOD 350



MOD 356



MOD 357







111

Parking Series Floor Tiles | Matt 30 x 30 cm



MPF 331



Parking Series Floor Tiles | Matt 30 x 30 cm



MPF 330



MPF 335



MPF 332



MPF 336



MPF 334



MPF 337



MPF 339









112 🐠 🚺 🚷

TECHNICAL SPECIFICATIONS & PACKAGING DETAILS WALL TILES

Worl	k Size	Pcs / Box	Coverage / Box	Weight (Approx.)	Box / Pattet	Coverage / Pattet
Dimensions (in mm)	Thickness (in mm)	(nos)	(sqft)	(kgs)	(nos)	(sqft)
200 x 300	7.2 x 7.4	25	16.00	18.9 ± 0.1	48	768
250 x 400	8.0 x 8.2	10	10.76	14.2 ± 0.1	48	516.48
300 x 450	9.0 x 9.2	08	11.3333	16.2 ± 0.1	48	543.9984
300 x 600	9.9 x 10.2	06	11.33	19.8 ± 0.1	40	453.2

Conformity of X Monalisa tiles to International Standards B IIIa ISO-13006:2012 and Bangladesh Standards IS-15622:2006

	Characteristics	Test Method	International Standard	Bangladesh Standard	Our Value
‡	Deviation in Length & Width		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.3%
7	Deviation in Thickness		Max. ± 0.5%	Max. ± 0.4%	Max. ± 0.4%
>− €	Surface Flatness (Warpage)	ISO 10545 (Part 2)	Max. ± 0.5%	Max. ± 0.4%	Max. ± 0.4%
7 *	Rectangularity (Straightness)		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.45%
<u> </u>	Surface Quality		95% free from visible defects.	95% free from visible defects.	95% free from visible defects.
	Scratch Hardness of Surface (Mohs)		Min. 3	Min. 3	Min. 3
•	Water Absorption	ISO 10545 (Part 3)	≥ 15%	≥ 15%	15≥ 18%
影	Crazing Resistance	ISO 10545 (Part 11)	Required	Min. 4cycles @7.5 bar	Min. 4cycles @7.5 bar
À	Chemical Resistance	ISO 10545 (Part 13)	No Damage	No Damage	No Damage
<u>↓</u>	Modulus of Rupture in N/mm²	ISO 10545 (Part 4)	Min. 150 kg/cm²	Min. 150 kg/cm²	Min. 160 kg/cm²
*	Thermal Shock Resistance	ISO 10545 (Part 9)	No Damage	No Damage	No Damage
@	Visual Inspection				The Tiles are Rectangular / Square in shap Flat and free from flows and other manufacturing defects.

TECHNICAL SPECIFICATIONS & PACKAGING DETAILS ROCK X | WALL TILES

Work S	Work Size		Coverage / Box	Coverage / Box Weight / Box (Approx.)		Coverage / Pallet
Dimensions (in mm)	Thickness (in mm)	(nos)	(sqft)	(kgs)	(nos)	(sqft)
300 x 600	8.0 - 8.2	5	9.68	15.0 ± 0.1	56	542.08

Conformity of X Monalisa tiles to International Standards B IIIa ISO-13006:2012 and Bangladesh Standards IS-15622:2006

Characteristics		Test Method	International Standard	Bangladesh Standard	Our Value	
1 =	Deviation in Length & Width					
	a. The deviation in percent of the average size of each tile (2 or 4 sides) from the work size (W)		Max. ± 0.6%	Max. ± 0.5%	Max. ± 0.3%	
	 b. The deviation in percent of the average size of each tile (2 or 4 sides) from the average size of the 10 test specimen (20 or 40 sides) 		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.3%	
7	Deviation in Thickness		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.4%	
—):	Deviation in Straightness of sides		Max. ± 0.5%	Max. ± 0.3%	Max. ± 0.2%	
	Deviation in Rectangularity	ISO 10545 (Part 2)	Max. ± 0.6%	Max. ± 0.3%	Max. ± 0.4%	
→	Surface Flatness					
4	a. Centre curvature (max.)		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.2%	
×	b. Edge curvature (max.)		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.2%	
<u>~~</u>	c. diagonal warpage (max.)		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.3%	
A	Surface Quality		Min. 95% free from visible defects	Min. 95% free from visible defects	Min. 95% free from visible defects	
•	Water Absorption	ISO 10545 (Part 3)	< 3.0%	< 3.0%	< 0.5%	
2	Scratch Hardness (Moh's Scale)	ISO 10545 (Part 2)/ EN 101	Min. 5	Min. 5	Min. 6	
⊜	Abrasion Resistance	ISO 10545 (Part 7)	Manufacturer to state abrassion class	Manufacturer to state abrassion class	PEI 4	
野	Crazing Resistance	ISO 10545 (Part 11)	Min. 4 cycles @7.5 bar min.	Min. 4 cycles @7.5 bar min.	Passed	
À	Chemical Resistance	ISO 10545 (Part 13)	Required, if Agreed	Required, if Agreed	Resistance to all acids and alkali (except HF and its compound)	
* *	Modulus of Rupture in N/mm²	ISO 10545 (Part 4)	Avg. 32, Individual min. 30	Avg. 30, Individual min. 30	Avg. 32, Individual min. 30	
×D	Thermal Shock Resistance	ISO 10545 (Part 9)	Required	Min. 10 Cycles	Min. 10 Cycles	
À	Resistance to household chemicals	ISO 10545 (Part 13)	Class AA min.	Class AA min.	Class AA min.	
4.4	Resistance to staining	ISO 10545 (Part 14)	Class 1 min.	Class 1 min.	Class 1 min.	
@	Visual Inspection				The Tiles are Rectangular / Square in shape, Flat and free from flaws and other manufacturing defects.	

TECHNICAL SPECIFICATIONS & PACKAGING DETAILS NANO MIRROR POLISHED TILES

Work	(Size	Pcs / Box	Coverage / Box	Weight (Approx.)	Box / Pattet	Coverage / Pattet
Dimensions (in mm)	Thickness (in mm)	(nos)	(sqft)	(kgs)	(nos)	(sqft)
600 x 600	9.9 x 10.2	4	15.50	32.2 ± 0.2	28	434
800 x 800	11.2 x 11.5	2	13.77	33.6 ± 0.2	20	275.4

Conformity of X Monalisa tiles to International Standards B Illa ISO-13006:2012 and Bangladesh Standards IS-15622:2006

	Characteristics	Test Method	International Standard	Bangladesh Standard	Our Value
: <u></u>	Deviation in Length & Width		Max. ± 0.6%	Max. ± 0.6%	Max. ± 0.2%
4	Deviation in Thickness		Max. ± 5.0%	Max. ± 5.0%	Max. ± 4.0%
	Straightness of sides		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.2%
-	Rectangularity		Max. ± 0.6%	Max. ± 0.5%	Max. ± 0.2%
>- <	Surface Flatness		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.2%
₩	a. Centre curvature (max.)	ISO 10545 (Part 2)	Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.2%
×	b. Edge curvature (max.)		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.2%
<u>~</u>	c. Diagonal warpage (max.)		Max. ± 0.5%	Max. ± 0.5%	Max. ± 0.2%
	Surface Quality		Min. 95% free from visible defects.	Min. 95% free from visible defects.	Min. 95% free from visible defects
•	Water Absorption		E, 0.5% ≤ Individual max. 0.6%	E, 0.5% ≤ Individual max. 0.6%	≤ 0.5%
<u>↓</u>	Modulus of Rupture in N/mm²	ISO 10545 (Part 3)	35, Individual min. 32	Avg. 35 N/mm², Individual Min. 32	Avg. 38 N/mm²
<u></u>	Breaking Strength in N ≥ 7.5 thickness < 7.5 thickness	ISO 10545 (Part 4)	Min. 1300 Min. 700	Min. 1300 Min. 700	Min. 2000 Min. 1000
2	Scratch Hardness (Moh's Scale)	ISO 10545 (Part 2)/EN101	No Required	No Required	Min. 5
<u>/*\</u>	Resistance to Surface Abrasion (of tiles intended for use of Floors)	ISO 10545 (Part 7)	Abrasion class shall be specified by the manufacturer	Abrasion class shall be specified by the manufacturer	PEI group IV
\leftrightarrow	Co-efficient of Linear Thermal Expansion from ambient temperture to 100 °C (K¹)	ISO 10545 (Part 4)	9 x 10 ⁴ k ¹ max.	x 10 ⁴ k ¹ max.	7 x 10 ⁴ k ¹ max.
×D	Thermal Stock Resistance	ISO 10545 (Part 9)	Min. 10 Cycles	Min. 10 Cycles	Passed
33	Crazing Resistance	ISO 10545 (Part 11)	4 Cycles	4 Cycles	Passed
*	Frost Resistance	ISO 10545 (Part 12)	No Damage	No Damage	Passed
×D	Impact Resistance	ISO 10545 (Part 5)	As per Mfg.	As per Mfg.	Min. 0.55
4.4	Resistance to Staining	ISO 10545 (Part 14)	Resistance	Resistance	Resistance
A	Resistance to household Chemicals	ISO 10545 (Part 13)	Class AA MIN.	Class AA MIN.	Class AA MIN.
À	Chemical Resistance	ISO 10545 (Part 13)	Required, if Agreed	Required, if Agreed	Resistance to all acids and alkalie (except HF and its compound)
•	Small Color Differences	ISO 10545 (Part 16)	Plain colored tiles only where required GL: <1.0	Plain colored tiles only where required GL:<0.75 UGL-1	As per Mfg.

TECHNICAL SPECIFICATIONS & PACKAGING DETAILS GERMI PROOF TILES

Product Size in mm	Thickness (in mm)	Avg. Wt/Box (In Kgs.)	No. of Tiles/ Box (In Pcs)	Coverage/Box
600x600mm	9.8-10.0	32.5	4	1.44sqm/ 15.5sft

Conformity of X Monalisa's tiles to International Standards B Illa ISO-13006:2012 and Bangladesh Standards IS-15622:2006

(Group B I a (WA ≤ 0.5%)

Symbols	Test Description	International STD	Monalisa`s Value
:	Deviation in Length & Width	±0.5	±0.25
7	Deviation in Thickness (%)	±5	±4
•	Straightness of Sides (%)	±0.5	±0.20
1	Rectangularity (%)	±0.5	±0.20
→ €	Surface Flatness (%)	±0.5	±0.20
<u>A</u>	Surface Quality	Min. 95% free from visible defects	95% free from visible defects
•	Water Absorption (%)	⊴0.5	<0.5
	Bulk Density (gm/cc)	Min. 2.2	Min. 2.3
<u>↓</u>	Modulus of Rupture (kg/cm2)	Avg. 350	>380
<u> </u>	Breaking Strength (N)	Min. 1600	Min. 2200
€.	Abrasion Resistance	As per Mfg.	Group v+
*	Frost Resistance	As specified by manufacturer	Resistance
S	Germi Proof (Anti Bac Test)	As per Mfg.	Passed (Test JIZ 2801:2015)
×)	Thermal Expansion	Co-efficient of linear thermal expansion ≤9x10 ⁻⁶ , (K ⁻¹)	Max. 8x10 ⁶
4.4	Stain Resistance	Min. Class 1	Min Class 1
₽	Scratch Hardness (Moh's scale)	Min. 6	Min. 8
B	Resistance to Chemical (Except HF) *Chemicals include household, swimming pool salts, acids & alkalls.	Min. Class AA	Min. Class AA

TECHNICAL SPECIFICATIONS & PACKAGING DETAILS STONE SHIELD

Work	k Size	Pcs / Box	Coverage / Box	Weight (Approx.)	Box / Pattet	Coverage / Pattet
Dimensions (in mm)	Thickness (in mm)	(nos)	(sqft)	(kgs)	(nos)	(sqft)
300 x 300	7.5 x 7.8	16	15.50	24.2 ± 0.1	42	451
400 x 400	10.3 x 10.5	8	13.60	30.8 ± 0.1	48	652.8
600 x 600	10.0 x 10.2	4	15.50	32.2 ± 0.2	28	434

Conformity of X Monalisa's tiles to International Standards B IIIa ISO-13006:2012 and Bangladesh Standards IS-15622:2006

	Characteristics	Test Method	International Standard	Bangladesh Standard	Our	Value
:	Deviation in Length & Width		Max. ± 0.6%	Max. ± 0.6%	Max.	± 0.2%
4	Deviation in Thickness		Max. ± 0.5%	Max. ± 5.0%	Max.	± 4.0%
	Straightness of sides	ISO 10545 (Part 2)	Max. ± 0.5%	Max. ± 0.5%	Max.	± 0.2%
	Rectangularity	130 10343 (Fait 2)	Max. ± 0.6%	Max. ± 0.6%	Max.	± 0.2%
>− ←	Surface Flatness		Max. ± 0.5%	Max. ± 0.15%	Max.	± 0.2%
•	Water Absorption	-	< 0.5, Max, 0.6	< 0.5, Max, 0.6	< 0).5%
-¥-	Apparent Density	DIN 51082	< 2.0 gm/cc	< 2.0 gm/cc	> 2.2 gm/cc	
<u>↓</u>	Modulus of Rupture in N/mm²	ISO 10545 (Part 4)	Min. 35 N/mm²	Min. 35 N/mm²	Min. 40 N/mm²	
<u> </u>	Breaking Strength	ISO 10545 (Part 4)	Min. 1300 N	Min. 1300 N	Min. 3000 N	
×D	Impact Resistance	ISO 10545 (Part 5)	As per Mfg.	Min. 0.55	Min.	. 0.55
/th	Surface Abrasion Resistance	ISO 10545 (Part 7)	As per Mfg.	As per Mfg.	PEI V+ (50000 + i	revolution passed)
2	Moh's Hardness	ISO 10545 (Part 2)/EN 101	Min. 5	Min. 5	Mi	n. 8
*	Frost Resistance	ISO 10545 (Part 12)	No Damage	No Damage	No Da	amage
*D	Thermal Shock Resistance	ISO 10545 (Part 9)	No Damage	No Damage	No Da	amage
B i	Thermal Expansion (COE)	ISO 10545 (Part 8)	Max. 9.0 x 10 ⁻⁶	Max. 9.0 x 10 ⁻⁶	Max. 6.5 x 10 ⁻⁶	
图	Crazing Resistance	ISO 10545 (Part 11)	4 Cycles	4 Cycles	Resis	stance
À	Chemical Resistance	ISO 10545 (Part 13)	No Damage	No Damage	No Damage	No Damage
d*	Stain Resistance	ISO 10545 (Part 14)	Resistance	Resistance	Resistance	Resistance

TECHNICAL SPECIFICATIONS & PACKAGING DETAILS

ROYAL PLANK TILES

Tough Planks are tiles with matching natural wood textures & gives exact look of wooden flooring.

Offers several advantages over actual wooden planks as mentioned below.

Royal Wo	Royal Wood Plank		
Water Resistant		Non-Resistant to Water	
Termite Resistence		Wood in Prone to Termites	
Long Lasting		Shorter Life	
Environment Friendly		Not Eco-Friendly	
Noise-Free While Moving		Wooden Flooring Makes Noise While Moving	
Very Easy to Lay		Complicated Laying Procedure	
Stain Resistant		Prone to Stains	

Application Area: Accent Wall, Bar/Restaurant, Bedroom, Commercial/Office, High Traffic, Hospitality, Living Room, Outdoor Area
Recommended Laying Pattern: Basketweave Pattern, Brick Pattern, Straight Pattern, Versailles Pattern

Work Size		Pieces / Box	Coverage / Box	Weight (Approx.)
Dimensions (in mm)	Thickness (in mm)	(nos)	(sqft)	(kgs)
150 x 600	9.9 - 10.2	10	9.68	19.6

Conformity of X Monalisa's tiles to International Standards B IIIa ISO-13006:2012 and Bangladesh Standards IS-15622:2006

Characteristics		Test Method	International Standard	Bangladesh Standard	Our Value
‡ =	Deviation in Length & Width		± 0.5%	± 0.4%	± 0.4%
-4	Deviation in Thickness		± 5%	± 4%	± 4%
) [±]	Straightness of Sides	ISO 10545-2	± 0.5%	± 0.3%	± 0.3%
1	Rectangularity		± 0.6%	± 0.4%	± 0.4%
> −←	Surface Flatness		± 0.5%	± 0.3%	± 0.3%
•	Water Absorption	ISO 10545-3	< 0.5%	< 0.5%	<0.5%
↑	Modulus of Rupture in N/mm²	ISO 10545-4	Min. 27 N/mm2	Min. 35 N/mm2	Min. 35 N/mm2
Q	Moisture Expansion	ISO 10545-10	0.04	0.02	0.02
2	Moh's Hardness	EN 101	Min. 3	Min. 5	Min. 5
*	Frost Resistance	ISO 10545-12	No Damage	No Damage	No Damage
×iD	Thermal Shock Resistance	ISO 10545-9	10 Cycle Min.	Passed	Passed
¥₽	Thermal Expansion (COE)	ISO 10545-8	9 x 10 ⁻⁶ K ⁻¹ Max.	8 x 10 ⁻⁶ K ⁻¹ Max.	8 x 10 ⁻⁶ K ⁻¹ Max.
E	Crazing Resistance	ISO 10545-11	4 Cycle @ 7.5 Bar Min.	Passed	Passed
<u>~</u>	Chemical Resistance	ISO 10545-13	Min. Class AA	Min. Class AA	Min. Class AA
4.4	Stain Resistance	ISO 10545-14	Min. Class-1	Min, Class-1	Min. Class-1

TECHNICAL SPECIFICATIONS & PACKAGING DETAILS OUT DOOR TILES

Work Size		Pcs / Box	Coverage / Box	Weight / Box (Approx.)	Box / Pattel	Coverage / Pallet
Dimensions (in mm)	Thickness (in mm)	(nos)	(sqft)	(kgs)	(nos)	(sqft)
300 x 300	9.6	10	9.68	19.25	54	522.72

Conformity of X Monalisa's tiles to International Standards B Illa ISO-13006:2012 and Bangladesh Standards IS-15622:2006

Characteristics		Test Method	International Standard	Bangladesh Standard	Our Value
‡ =	Deviation in Length & Width		± 0.5%	Max. ± 0.5%	± 0.4%
7	Deviation in Thickness		± 5%	Max. ± 0.4%	± 0.4%
) [±]	Straightness of sides	EN 98.EN ISO 10545-2	± 0.5%	Max. ± 0.5%	± 0.2%
J*	Rectangularity		± 0.6%	Max. ± 0.5%	± 0.4%
>− ←	Surface Flatness (%)		± 0.5%	Max. ± 0.5%	± 0.2%
<u> </u>	Surface Quality			Min. 95% free from visible defects	
•	Water Absorption	EN 98.EN ISO 10545-3	< 0.5%	< 3.0%	< 0.5%
A	Scratch Hardness (Moh's Scale)	EN 101	3	Not Required	5 above
مئد	Breaking Strength (N)	EN 98.EN ISO 10545-4	≥ 1300N	1500 min.	≥ 1400N
→	Modulus of Rupture N/mm²	EN 98.EN ISO 10545-4	27 N / mm²	Avg. 30, Individual min. 28	± 40 N / mm²
62.	Resistance to Surface Abrasion	EN 98.EN ISO 10545-7	Manufacturer to state abrasion class	Manufacturer to state abrasion class	N/A
E2	Crazing Resistance	EN 98.EN ISO 10545-11	No Crazing	Min. 4 cycles @7.5 bar min.	No Crazing
<u>A</u>	Chemical Resistance	EN 98.EN ISO 10545-13	No Damage	Required, if Agreed	No Damage
Q	Moisture Expansion	EN 98.EN ISO 10545-10	As Per Manufacturer	Nil	
*	Thermal Shock	EN 98.EN ISO 10545-9	No Damage	No Damage	No Damage
@	Visual Inspection				The tiles are rectangular in shape flate & free form flows & Other manufacturing Detects

TECHNICAL SPECIFICATIONS & PACKAGING DETAILS PARKING TILES

Work Size		Pcs / Box	Coverage / Box	Weight (Approx.)	Box / Pattet	Coverage / Pattet
Dimensions (in mm)	Thickness (in mm)	(nos)	(sqft)	(kgs)	(nos)	(sqft)
300 x 300	12.1 x 12.4	8	7.74	19.4 ± 0.1	54	417.96

Conformity of X Monalisa's tiles to International Standards B IIIa ISO-13006:2012 and Bangladesh Standards IS-15622:2006

	Characteristics	Test Method	International Standard	Bangladesh Standard	Our Value
‡	Deviation in Length & Width		± 0.6%	± 0.5%	± 0.2%
4	Deviation in Thickness		± 0.5%	± 0.4%	± 0.4%
) [±]	Straightness of sides	ISO 10545 (Part 2)	± 0.5%	± 0.5%	± 0.2%
	Rectangularity	,	± 0.6%	± 0.5%	± 0.2%
>	Surface Flatness (%)		± 0.5%	± 0.5%	± 0.3%
	Surface Quality		95% free from visible defects.	95% free from visible defects.	95% free from visible defects.
~	Water Absorption	ISO 10545 (Part 3)	< 3.0%	< 3.0%	< 3.5%
P	Scratch Hardness (Moh's Scale)	ISO 10545 (Part 2)/ EN 101	Not Required	Not Required	Min. 5
ش	Breaking Strength (N)	ISO 10545 (Part 4)	Thickness ≥ 7.5 mm 1300min	1500 min.	2500 min.
↓	Modulus of Rupture in N/mm²	ISO 10545 (Part 4)	Avg. 30, Individual Min. 28	Avg. 30, Individual Min. 28	Avg. 35, Individual Min. 32
62 ,	Resistance to Surface Abrasion	ISO 10545 (Part 7)	Manufacturer to state abrasion class	Manufacturer to state abrasion class	PEI 4
3	Crazing Resistance	ISO 10545 (Part 11)	Required	Required, if Agreed	Resistsnce
A	Chemical Resistance	ISO 10545 (Part 13)	Required, if Agreed	Min. 4 cycles @7.5 ber min.	Resistance to all acids and alkalies (except HF and its Compound)
€	Moisture Expansion	ISO 10545 (Part 10)	Nil	Nil	Nil
*	Thermal Shock	ISO 10545 (Part 9)	No Damage	No Damage	No Damage
@	Visual Inspection				The Tiles are Rectangular / Square in sha Flat and free from flows and other manufacturing defects.